



Indoor Delight

SPC COLLECTION



LI-ID14 Homewood Waltz

Indoor Delight offers sophisticated European oak designs using the latest EIR embossing technology with 8-10 repeats on film designs, delivering a premium look of rich and vivid floor in on-trend 6 feet x 9 inches planks. Its exclusive designs are unique and only available at Lions Floor, ensuring customers protection from competitors, while making flooring projects truly "limited edition". Indoor Delight is also waterproof, scratch-resistant, antibacterial-cured, easy to install, low-maintenance, environmentally friendly, durable, and long-lasting, making it appeal to both homeowners looking for an upgrade on their remodel, as well as builders in mid- to high-end new construction.



Water Resistant



Indent Resistant



Paw Friendly



Sound Tested



CERTIFIED BY
SCS Global Services

Indoor Delight

SPC COLLECTION

Specifications

Material Type	SPC
Plank Size	6' x 9"
Total Thickness	6.5 mm
Core Thickness	5 mm
Wear Layer	20 mil
Attached Pad	Yes
Pad Thickness	1.5 mm
Pad Type	Anti Bacterial & Acoustic
Edge Profile	Painted Bevel
Installation Type	Uniclic
Plank Repeat	8-10
Texture/Style	Embossed in Register (EIR)
Box Size	22.65 sq. ft.
Pieces/Box	5 pieces
Lbs./Box	50 lbs.
Pallet Size	40 boxes
Container Size	960 boxes



Colors



Moldings

Seamlessly blend together our high-performing flooring products with the desired trim to create the desired aesthetic.

Our moldings coordinate with all our collections and respected colors.



End Cap
35 mm x 10 mm
(1.378" x .394")



Flush Stair Nose
110.4 mm x 5.1 mm
(4.346" x .201")



Quarter Round
25.4 mm x 15.2 mm
(1.77" x .598")



Reducer
25.4 mm x 15.2 mm
(1.77" x .598")



T-Molding
45.4 mm x 3.9 mm
(1.787" x .154")

Testing

Fire Rating	ASTM E648	Class 1	Average Wear Layer Thickness	ASTM F410	19.9 mil
Coefficient of Friction	ASTM D2047	Standard Neolite 0.90	Dimensional Stability, Curl After Heat	ASTM F2199	Passes
Static Load Limit	ASTM F970	0.005 in.	Residual Indentation, Surface Integrity	ASTM F1914	Passes
IIC - Impact Sound Rating	E492	59 db	Resistance to Heat	ASTM F1514	Passes
STC - Sound Transmission Loss	E90	53 db	Resistance to Light	ASTM F1515	Passes
Overall Thickness	ASTM F387	0.264 in.	Floor Score Certified Phthalate Free		