

TEST REPORT

CLIENT Lions Floor

TEST METHOD CONDUCTED	ASTM F387 Standard Test Method for Measuring Thickness of
	Resilient Floor Covering with Foam Layer



DESCRIPTION OF TEST SAMPLE	
IDENTIFICATION	Lone Star Spirit Collection
COLOR	Saddle Brownie
ROLL NUMBER	SKU: LI-T\$106V1134P221210
CONSTRUCTION	SPC


GENERAL PRINCIPLE

The total thickness of a resilient flooring material is determined through measurements made using a .250 inch presser foot and a dial micrometer. The average of 5 total measurements is reported as the average total thickness.

TEST RESULTS

	THICKNESS
SPECIMEN 1	0.232 Inch
SPECIMEN 2	0.230 Inch
SPECIMEN 3	0.231 Inch
SPECIMEN 4	0.230 Inch
SPECIMEN 5	0.230 Inch

AVERAGE TOTAL THICKNESS	0.231 Inch
AVERAGE IOIAL IIIICKIVE33	0.231 111011



APPROVED BY:

Dary aslowing



This facility is accredited by the National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code 100297. This accreditation does not constitute an endorsement, certification, or approval by NIST or any agency of the United States Government for the producttested. This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples testedand is not necessarily indicative of apparently identical or similar products. This report, or the name of Professional Testing Laboratory, Inc. shall not be used under any circumstance in advertising to the general public.

